

BILL TO

Company Name: _____ Acct #: _____
Address: _____
City / State / Zip: _____
Phone: _____
Fax Number: _____

SHIP TO

Company Name: _____ Acct #: _____
Address: _____
City / State / Zip: _____
Phone: _____
Fax Number: _____

P.O. #: _____
Side Mark: _____
Contact: _____
Date: _____

Model Standard Cord Loop *	Qty	Width	Length	Color #	Color Name	Fabric Type Light Filtering Room Darkening	Mount Inside Outside Side	Loop Cord Placement Right/Left **	Hold Down Brackets Yes/No	Side-by-Side Blinds Yes/No	Spacer Blocks (0, 1, 2, 3)	Custom Cord Length ***	Extension Brackets Yes/No
S CL						LF RD	IB OB S	R L	Y N	Y N	0 1 2 3		Y N
S CL						LF RD	IB OB S	R L	Y N	Y N	0 1 2 3		Y N
S CL						LF RD	IB OB S	R L	Y N	Y N	0 1 2 3		Y N
S CL						LF RD	IB OB S	R L	Y N	Y N	0 1 2 3		Y N
S CL						LF RD	IB OB S	R L	Y N	Y N	0 1 2 3		Y N

* The Standard Hardware System is only available with fabrics in the base collection. Fabrics from the Personal Color System and Limited Edition Collections are only available with the Continuous Cord Loop System. ** On blinds built with the Standard Hardware System, the cord which adjusts the vanes will always be located on the left side of the blind, lift cord on right. *** The Custom Cord Length column only applies to blinds with the Continuous Cord Loop System. Continuous Cord Loops come in 2-foot to 15-foot lengths in 1-foot intervals. Please specify length. PLEASE NOTE: Odysee Blinds over 25 square feet must be built with Continuous Cord Loop Hardware. Please see the *Odysee Insulating Blinds Manufacturers Price List and Reference Guide* for details.

SPECIAL INSTRUCTIONS

**Odysee Measuring Instructions
Inside or Side Mount**

Use a steel tape to measure the opening at three different places, and use the narrowest dimension when ordering. Be exact! The factory will make the vanes narrower so they will not rub against the window casing. Measure the height of the window from the top (soffit) down to the sill.

Outside Mount

Use a steel tape to measure the exact length and width of the area to be covered. It is recommended that the blinds overlap the window by at least 1½" on each side. When installation has no sill, allow the blind to overlap the bottom of the window casing by at least 1½". Blind fabric will measure width indicated on the order form.

Shipping Charges - Comfortex will ship all orders for fabricated shades freight free via UPS, FedEx Ground or other similar method within the continental United States. Shades with widths of 98" or more do not meet the size and weight requirements of UPS or FedEx Ground are required to ship by motor freight. A \$65.00 Common Carrier surcharge will be added for all orders shipped within the continental United States which required to ship by motor freight. A per unit transportation surcharge will be added to all orders. See freight policy at www.comfortexdealers.com for more details and for freight policy for Hawaii and Alaska.

Customer Signature _____ Date ____/____/____ Measured By _____ Date ____/____/____